BINAR EXECUTIVE

designed — INCLASS Studio



All GREENGUARD Gold Certified products are on <u>UL.SPOT</u>.
Please visit it for the latest update.



INCLASS

Colección



Sillón con respaldo medio y base de 4 radios de aluminio BIN0220 <u>certificado +</u>



Sillón con respaldo medio (base giratoria de 5 radios de aluminio con ruedas + elevación con gas) BINO210 <u>certificado +</u>



Sillón con respaldo medio (base giratoria 5 radios de aluminio con ruedas + basculante) BINO215 <u>certificado +</u>



Sillón con respaldo medio (base giratoria 5 radios de aluminio con ruedas + sincro) BINO218 <u>certificado +</u>



Sillón con respaldo alto y base de 4 radios de aluminio BIN0320 <u>certificado +</u>



Sillón con respaldo alto (base giratoria de 5 radios de aluminio con ruedas + elevación con gas) BIN0310 <u>certificado +</u>



Sillón con respaldo alto (base giratoria 5 radios de aluminio con ruedas + basculante) BIN0315 <u>certificado +</u>



Sillón con respaldo alto (base giratoria 5 radios de aluminio con ruedas + sincro) BINO318 <u>certificado +</u>



INCLASS

BINAR EXECUTIVE Armchair with medium back and 4 spoke aluminum swivel base

Restrictions: Excludes genuine leather option

260934-410

Certificate Number

05/05/2022 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

BINAR EXECUTIVE Armchair with medium back (5 spoke aluminum swivel base on casters + gas lift)

Restrictions: Excludes genuine leather option

260936-410

Certificate Number

05/05/2022 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

BINAR EXECUTIVE Armchair with medium back (5 spoke aluminum swivel base on casters + gas lift + tilt mechanism)

Restrictions: Excludes genuine leather option

260938-410

Certificate Number

05/05/2022 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

BINAR EXECUTIVE Armchair with medium back (5 spoke aluminum swivel base on casters + gas lift + synchro mechanism)

Restrictions: Excludes genuine leather option

260940-410

Certificate Number

05/05/2022 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

BINAR EXECUTIVE Armchair with high back and 4 spoke aluminum swivel base

Restrictions: Excludes genuine leather option

260935-410

Certificate Number

05/05/2022 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

BINAR EXECUTIVE Armchair with high back (5 spoke aluminum swivel base on casters + gas lift)

Restrictions: Excludes genuine leather option

260937-410

Certificate Number

05/05/2022 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (c)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

BINAR EXECUTIVE Armchair with high back (5 spoke aluminum swivel base on casters + gas lift + tilt mechanism)

Restrictions: Excludes genuine leather option

260939-410

Certificate Number

05/05/2022 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

BINAR EXECUTIVE Armchair with high back (5 spoke aluminum swivel base on casters + gas lift + synchro mechanism)

Restrictions: Excludes genuine leather option

260941-410

Certificate Number

05/05/2022 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).