

GOLD

All GREENGUARD Gold Certified products are on <u>UL.SPOT</u>. Please visit it for the latest update.

### KORI designed — Florent Coirier



#### **INCLASS**

#### Overview



Swivel armchair with high back (5 spoke aluminum swivel base on casters + gas lift + tilt mechanism) KOR0310 certificated+



Swivel chair with high back (5 spoke aluminum swivel base on casters + gas lift + tilt mechanism) KOR0010 certificated+



Swivel armchair with medium back (5 spoke aluminum swivel base on casters + gas lift + tilt mechanism) KOR0410 certificated+



Swivel chair with medium back (5 spoke aluminum swivel base on casters + gas lift + tilt mechanism) KOR0110 certificated+



Swivel armchair with low back (5 spoke aluminum swivel base on casters + gas lift + tilt mechanism) KOR0510 certificated+



Swivel chair with low back (5 spoke aluminum swivel base on casters + gas lift + tilt mechanism) KOR0210 certificated+



Swivel armchair with high back (5 spoke aluminum swivel base on casters + gas lift + 7 position tilt mechanism) KOR0320 certificated+



Swivel chair with high back (5 spoke aluminum swivel base on casters + gas lift + 7 position tilt mechanism) KOR0020 certificated+



Swivel armchair with medium back (5 spoke aluminum swivel base on casters + gas lift + 7 position tilt mechanism KOR0420 certificated+



spoke aluminum swivel base on casters + gas lift + 7 position tilt mechanism) KOR0120 certificated+



Swivel chair with medium back (5 spoke aluminum swivel base on casters + aas lift) KOR0130 certificated+



spoke aluminum swivel base) KOR0140 certificated+



Swivel armchair with low back (5 spoke aluminum swivel base on casters + gas lift + 7 position tilt mechanism) KOR0520 certificated+



Swivel chair with low back (5 spoke aluminum swivel base on casters + gas lift + 7 position tilt mechanism) KOR0220 certificated+



Swivel armchair with high back (5 spoke aluminum swivel base on casters + gas lift) KOR0330 certificated+



Swivel armchair with high back (4 spoke aluminum swivel base) KOR0340 certificated+



Swivel chair with high back (5 spoke aluminum swivel base on casters + aas lift) KOR0030 certificated+



Swivel chair with high back (4 spoke aluminum swivel base) KOR0040 certificated+

Swivel armchair with medium back

(5 spoke aluminum swivel base on

casters + gas lift)

KOR0430 certificated+

Swivel armchair with medium back (4 spoke aluminum swivel base) KOR0440 certificated+



Swivel chair with medium back (4



Swivel armchair with low back (5

spoke aluminum swivel base on

casters + gas lift)

Swivel armchair with low back (4 spoke aluminum swivel base) KOR0540 certificated+



Swivel chair with low back (4 spoke aluminum swivel base) KOR0240 certificated+



Swivel chair with low back (5 spoke aluminum swivel base on casters + gas lift) KOR0230 certificated+





PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS UL.COM/GG UL 2818

### INCLASS

KORI Swivel armchair with high back (5 spoke aluminum swivel base on casters + gas lift + tilt mechanism) 301610-410 Certificate Number

05/15/2023 - 04/27/2026

**Certificate** Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.

Furniture and furnishings are tested in accordance with ANSI/BIFMA M7.1-2011 and determined to comply with ANSI/BIFMA X7.1-2011 and ANSI/BIFMA e3-2012 Credit 7.6.1. Seating products are modeled in the seating environment.



#### **GREENGUARD Certification Criteria for Mattresses, Bedding, Component Materials and** Seating Units

Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC <sub>(A)</sub>	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	µg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	µg/m³
Individual VOCs (D)	-	1/10th TLV	-

(A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.

- (B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.
- <sup>(C)</sup> Applicable to flooring and furniture, including component materials.
- (D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).





PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS UL.COM/GG UL 2818

### INCLASS

KORI Swivel armchair with high back (5 spoke aluminum swivel base on casters + gas lift + 7 position tilt mechanism) 301611-410 Certificate Number

05/15/2023 - 04/27/2026

**Certificate** Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.

Furniture and furnishings are tested in accordance with ANSI/BIFMA M7.1-2011 and determined to comply with ANSI/BIFMA X7.1-2011 and ANSI/BIFMA e3-2012 Credit 7.6.1. Seating products are modeled in the seating environment.



#### **GREENGUARD Certification Criteria for Mattresses, Bedding, Component Materials and** Seating Units

Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC <sub>(A)</sub>	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	µg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	µg/m³
Individual VOCs (D)	-	1/10th TLV	-

(A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.

- (B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.
- <sup>(C)</sup> Applicable to flooring and furniture, including component materials.
- (D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).





PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS UL.COM/GG UL 2818

### INCLASS

KORI Swivel armchair with high back (5 spoke aluminum swivel base on casters + gas lift) 301612-410 Certificate Number

05/15/2023 - 04/27/2026

**Certificate** Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.

Furniture and furnishings are tested in accordance with ANSI/BIFMA M7.1-2011 and determined to comply with ANSI/BIFMA X7.1-2011 and ANSI/BIFMA e3-2012 Credit 7.6.1. Seating products are modeled in the seating environment.



#### **GREENGUARD Certification Criteria for Mattresses, Bedding, Component Materials and** Seating Units

Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC <sub>(A)</sub>	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	µg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	µg/m³
Individual VOCs (D)	-	1/10th TLV	-

(A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.

- (B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.
- <sup>(C)</sup> Applicable to flooring and furniture, including component materials.
- (D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).





PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS UL.COM/GG UL 2818

### INCLASS

KORI Swivel armchair with high back (4 spoke aluminum swivel base) 301613-410 Certificate Number

05/15/2023 - 04/27/2026

**Certificate** Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.

Furniture and furnishings are tested in accordance with ANSI/BIFMA M7.1-2011 and determined to comply with ANSI/BIFMA X7.1-2011 and ANSI/BIFMA e3-2012 Credit 7.6.1. Seating products are modeled in the seating environment.



#### **GREENGUARD Certification Criteria for Mattresses, Bedding, Component Materials and** Seating Units

Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC <sub>(A)</sub>	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	µg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	µg/m³
Individual VOCs (D)	-	1/10th TLV	-

(A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.

- (B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.
- <sup>(C)</sup> Applicable to flooring and furniture, including component materials.
- (D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).





PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS UL.COM/GG UL 2818

### INCLASS

KORI Swivel chair with high back (5 spoke aluminum swivel base on casters + gas lift + tilt mechanism) 301614-410 Certificate Number

05/15/2023 - 04/27/2026

**Certificate** Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.

Furniture and furnishings are tested in accordance with ANSI/BIFMA M7.1-2011 and determined to comply with ANSI/BIFMA X7.1-2011 and ANSI/BIFMA e3-2012 Credit 7.6.1. Seating products are modeled in the seating environment.



#### **GREENGUARD Certification Criteria for Mattresses, Bedding, Component Materials and** Seating Units

Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC <sub>(A)</sub>	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	µg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	µg/m³
Individual VOCs (D)	-	1/10th TLV	-

(A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.

- (B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.
- <sup>(C)</sup> Applicable to flooring and furniture, including component materials.
- (D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).





PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS UL.COM/GG UL 2818

### INCLASS

KORI Swivel chair with high back (5 spoke aluminum swivel base on casters + gas lift + 7 position tilt mechanism) 301615-410 Certificate Number

05/15/2023 - 04/27/2026

**Certificate Period** 

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.

Furniture and furnishings are tested in accordance with ANSI/BIFMA M7.1-2011 and determined to comply with ANSI/BIFMA X7.1-2011 and ANSI/BIFMA e3-2012 Credit 7.6.1. Seating products are modeled in the seating environment.



#### **GREENGUARD Certification Criteria for Mattresses, Bedding, Component Materials and** Seating Units

Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC <sub>(A)</sub>	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	µg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	µg/m³
Individual VOCs (D)	-	1/10th TLV	-

(A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.

- (B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.
- <sup>(C)</sup> Applicable to flooring and furniture, including component materials.
- (D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).





PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS UL.COM/GG UL 2818

### INCLASS

KORI Swivel chair with high back (5 spoke aluminum swivel base on casters + gas lift) 301616-410 Certificate Number

05/15/2023 - 04/27/2026

**Certificate** Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.

Furniture and furnishings are tested in accordance with ANSI/BIFMA M7.1-2011 and determined to comply with ANSI/BIFMA X7.1-2011 and ANSI/BIFMA e3-2012 Credit 7.6.1. Seating products are modeled in the seating environment.



#### **GREENGUARD Certification Criteria for Mattresses, Bedding, Component Materials and** Seating Units

Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC <sub>(A)</sub>	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	µg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	µg/m³
Individual VOCs (D)	-	1/10th TLV	-

(A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.

- (B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.
- <sup>(C)</sup> Applicable to flooring and furniture, including component materials.
- (D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).





PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS UL.COM/GG UL 2818

### INCLASS

KORI Swivel chair with high back (4 spoke aluminum swivel base) 301617-410 Certificate Number

05/15/2023 - 04/27/2026

**Certificate** Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.

Furniture and furnishings are tested in accordance with ANSI/BIFMA M7.1-2011 and determined to comply with ANSI/BIFMA X7.1-2011 and ANSI/BIFMA e3-2012 Credit 7.6.1. Seating products are modeled in the seating environment.



#### **GREENGUARD Certification Criteria for Mattresses, Bedding, Component Materials and** Seating Units

Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC <sub>(A)</sub>	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	µg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	µg/m³
Individual VOCs (D)	-	1/10th TLV	-

(A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.

- (B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.
- <sup>(C)</sup> Applicable to flooring and furniture, including component materials.
- (D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).





PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS UL.COM/GG UL 2818

### INCLASS

KORI Swivel armchair with medium back (5 spoke aluminum swivel base on casters + gas lift + tilt mechanism) 301618-410 Certificate Number

05/15/2023 - 04/27/2026

**Certificate** Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.

Furniture and furnishings are tested in accordance with ANSI/BIFMA M7.1-2011 and determined to comply with ANSI/BIFMA X7.1-2011 and ANSI/BIFMA e3-2012 Credit 7.6.1. Seating products are modeled in the seating environment.



#### **GREENGUARD Certification Criteria for Mattresses, Bedding, Component Materials and** Seating Units

Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC <sub>(A)</sub>	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	µg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	µg/m³
Individual VOCs (D)	-	1/10th TLV	-

(A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.

- (B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.
- <sup>(C)</sup> Applicable to flooring and furniture, including component materials.
- (D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).





PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS UL.COM/GG UL 2818

### INCLASS

KORI Swivel armchair with medium back (5 spoke aluminum swivel base on casters + gas lift + 7 position tilt mechanism) 301619-410 Certificate Number

05/15/2023 - 04/27/2026

**Certificate** Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.

Furniture and furnishings are tested in accordance with ANSI/BIFMA M7.1-2011 and determined to comply with ANSI/BIFMA X7.1-2011 and ANSI/BIFMA e3-2012 Credit 7.6.1. Seating products are modeled in the seating environment.



#### **GREENGUARD Certification Criteria for Mattresses, Bedding, Component Materials and** Seating Units

Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC <sub>(A)</sub>	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	µg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	µg/m³
Individual VOCs (D)	-	1/10th TLV	-

(A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.

- (B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.
- <sup>(C)</sup> Applicable to flooring and furniture, including component materials.
- (D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).





PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS UL.COM/GG UL 2818

### INCLASS

KORI Swivel armchair with medium back (5 spoke aluminum swivel base on casters + gas lift) 301620-410 Certificate Number

05/15/2023 - 04/27/2026

**Certificate** Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.

Furniture and furnishings are tested in accordance with ANSI/BIFMA M7.1-2011 and determined to comply with ANSI/BIFMA X7.1-2011 and ANSI/BIFMA e3-2012 Credit 7.6.1. Seating products are modeled in the seating environment.



#### **GREENGUARD Certification Criteria for Mattresses, Bedding, Component Materials and** Seating Units

Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC <sub>(A)</sub>	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	µg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	µg/m³
Individual VOCs (D)	-	1/10th TLV	-

(A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.

- (B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.
- <sup>(C)</sup> Applicable to flooring and furniture, including component materials.
- (D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).





PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS UL.COM/GG UL 2818

### INCLASS

KORI Swivel armchair with medium back (4 spoke aluminum swivel base) 301621-410 Certificate Number

05/15/2023 - 04/27/2026

**Certificate** Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.

Furniture and furnishings are tested in accordance with ANSI/BIFMA M7.1-2011 and determined to comply with ANSI/BIFMA X7.1-2011 and ANSI/BIFMA e3-2012 Credit 7.6.1. Seating products are modeled in the seating environment.



#### **GREENGUARD Certification Criteria for Mattresses, Bedding, Component Materials and** Seating Units

Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC <sub>(A)</sub>	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	µg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	µg/m³
Individual VOCs (D)	-	1/10th TLV	-

(A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.

- (B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.
- <sup>(C)</sup> Applicable to flooring and furniture, including component materials.
- (D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).





PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS UL.COM/GG UL 2818

### INCLASS

KORI Swivel chair with medium back (5 spoke aluminum swivel base on casters + gas lift + tilt mechanism) 301622-410 Certificate Number

05/15/2023 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.

Furniture and furnishings are tested in accordance with ANSI/BIFMA M7.1-2011 and determined to comply with ANSI/BIFMA X7.1-2011 and ANSI/BIFMA e3-2012 Credit 7.6.1. Seating products are modeled in the seating environment.



#### **GREENGUARD Certification Criteria for Mattresses, Bedding, Component Materials and** Seating Units

Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC <sub>(A)</sub>	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	µg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	µg/m³
Individual VOCs (D)	-	1/10th TLV	-

(A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.

- (B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.
- <sup>(C)</sup> Applicable to flooring and furniture, including component materials.
- (D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).





PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS UL.COM/GG UL 2818

### INCLASS

KORI Swivel chair with medium back (5 spoke aluminum swivel base on casters + gas lift + 7 position tilt mechanism) 301623-410 Certificate Number

05/15/2023 - 04/27/2026

**Certificate** Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.

Furniture and furnishings are tested in accordance with ANSI/BIFMA M7.1-2011 and determined to comply with ANSI/BIFMA X7.1-2011 and ANSI/BIFMA e3-2012 Credit 7.6.1. Seating products are modeled in the seating environment.



#### **GREENGUARD Certification Criteria for Mattresses, Bedding, Component Materials and** Seating Units

Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC <sub>(A)</sub>	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	µg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	µg/m³
Individual VOCs (D)	-	1/10th TLV	-

(A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.

- (B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.
- <sup>(C)</sup> Applicable to flooring and furniture, including component materials.
- (D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).





PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS UL.COM/GG UL 2818

### INCLASS

KORI Swivel chair with medium back (5 spoke aluminum swivel base on casters + gas lift) 301624-410 Certificate Number

05/15/2023 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.

Furniture and furnishings are tested in accordance with ANSI/BIFMA M7.1-2011 and determined to comply with ANSI/BIFMA X7.1-2011 and ANSI/BIFMA e3-2012 Credit 7.6.1. Seating products are modeled in the seating environment.



#### **GREENGUARD Certification Criteria for Mattresses, Bedding, Component Materials and** Seating Units

Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC <sub>(A)</sub>	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	µg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	µg/m³
Individual VOCs (D)	-	1/10th TLV	-

(A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.

- (B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.
- <sup>(C)</sup> Applicable to flooring and furniture, including component materials.
- (D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).





PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS UL.COM/GG UL 2818

### INCLASS

KORI Swivel chair with medium back (4 spoke aluminum swivel base) 301625-410 Certificate Number

05/15/2023 - 04/27/2026

**Certificate** Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.

Furniture and furnishings are tested in accordance with ANSI/BIFMA M7.1-2011 and determined to comply with ANSI/BIFMA X7.1-2011 and ANSI/BIFMA e3-2012 Credit 7.6.1. Seating products are modeled in the seating environment.



#### **GREENGUARD Certification Criteria for Mattresses, Bedding, Component Materials and** Seating Units

Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC <sub>(A)</sub>	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	µg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	µg/m³
Individual VOCs (D)	-	1/10th TLV	-

(A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.

- (B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.
- <sup>(C)</sup> Applicable to flooring and furniture, including component materials.
- (D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).





PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS UL.COM/GG UL 2818

### INCLASS

KORI Swivel armchair with low back (5 spoke aluminum swivel base on casters + gas lift + tilt mechanism) 301626-410 Certificate Number

05/15/2023 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.

Furniture and furnishings are tested in accordance with ANSI/BIFMA M7.1-2011 and determined to comply with ANSI/BIFMA X7.1-2011 and ANSI/BIFMA e3-2012 Credit 7.6.1. Seating products are modeled in the seating environment.



#### **GREENGUARD Certification Criteria for Mattresses, Bedding, Component Materials and** Seating Units

Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC <sub>(A)</sub>	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	µg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	µg/m³
Individual VOCs (D)	-	1/10th TLV	-

(A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.

- (B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.
- <sup>(C)</sup> Applicable to flooring and furniture, including component materials.
- (D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).





PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS UL.COM/GG UL 2818

### INCLASS

KORI Swivel armchair with low back (5 spoke aluminum swivel base on casters + gas lift + 7 position tilt mechanism) 301627-410 Certificate Number

05/15/2023 - 04/27/2026

**Certificate** Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.

Furniture and furnishings are tested in accordance with ANSI/BIFMA M7.1-2011 and determined to comply with ANSI/BIFMA X7.1-2011 and ANSI/BIFMA e3-2012 Credit 7.6.1. Seating products are modeled in the seating environment.



#### **GREENGUARD Certification Criteria for Mattresses, Bedding, Component Materials and** Seating Units

Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC <sub>(A)</sub>	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	µg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	µg/m³
Individual VOCs (D)	-	1/10th TLV	-

(A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.

- (B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.
- <sup>(C)</sup> Applicable to flooring and furniture, including component materials.
- (D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).





PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS UL.COM/GG UL 2818

### INCLASS

KORI Swivel armchair with low back (5 spoke aluminum swivel base on casters + gas lift) 301628-410 Certificate Number

05/15/2023 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.

Furniture and furnishings are tested in accordance with ANSI/BIFMA M7.1-2011 and determined to comply with ANSI/BIFMA X7.1-2011 and ANSI/BIFMA e3-2012 Credit 7.6.1. Seating products are modeled in the seating environment.



#### **GREENGUARD Certification Criteria for Mattresses, Bedding, Component Materials and** Seating Units

Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC <sub>(A)</sub>	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	µg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	µg/m³
Individual VOCs (D)	-	1/10th TLV	-

(A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.

- (B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.
- <sup>(C)</sup> Applicable to flooring and furniture, including component materials.
- (D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).





PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS UL.COM/GG UL 2818

### INCLASS

KORI Swivel armchair with low back (4 spoke aluminum swivel base) 301629-410 Certificate Number

05/15/2023 - 04/27/2026

**Certificate** Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.

Furniture and furnishings are tested in accordance with ANSI/BIFMA M7.1-2011 and determined to comply with ANSI/BIFMA X7.1-2011 and ANSI/BIFMA e3-2012 Credit 7.6.1. Seating products are modeled in the seating environment.



#### **GREENGUARD Certification Criteria for Mattresses, Bedding, Component Materials and** Seating Units

Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC <sub>(A)</sub>	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	µg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	µg/m³
Individual VOCs (D)	-	1/10th TLV	-

(A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.

- (B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.
- <sup>(C)</sup> Applicable to flooring and furniture, including component materials.
- (D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).





PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS UL.COM/GG UL 2818

### INCLASS

KORI Swivel chair with low back (5 spoke aluminum swivel base on casters + gas lift + tilt mechanism)

301630-410 Certificate Number

05/15/2023 - 04/27/2026

**Certificate** Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.

Furniture and furnishings are tested in accordance with ANSI/BIFMA M7.1-2011 and determined to comply with ANSI/BIFMA X7.1-2011 and ANSI/BIFMA e3-2012 Credit 7.6.1. Seating products are modeled in the seating environment.



#### **GREENGUARD Certification Criteria for Mattresses, Bedding, Component Materials and** Seating Units

Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC <sub>(A)</sub>	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	µg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	µg/m³
Individual VOCs (D)	-	1/10th TLV	-

(A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.

- (B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.
- <sup>(C)</sup> Applicable to flooring and furniture, including component materials.
- (D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).





PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS UL.COM/GG UL 2818

### INCLASS

KORI Swivel chair with low back (5 spoke aluminum swivel base on casters + gas lift + 7 position tilt mechanism) 301631-410 Certificate Number

05/15/2023 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.

Furniture and furnishings are tested in accordance with ANSI/BIFMA M7.1-2011 and determined to comply with ANSI/BIFMA X7.1-2011 and ANSI/BIFMA e3-2012 Credit 7.6.1. Seating products are modeled in the seating environment.



#### **GREENGUARD Certification Criteria for Mattresses, Bedding, Component Materials and** Seating Units

Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	µg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	µg/m³
Individual VOCs (D)	-	1/10th TLV	-

(A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.

- (B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.
- <sup>(C)</sup> Applicable to flooring and furniture, including component materials.
- (D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).





PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS UL.COM/GG UL 2818

### INCLASS

KORI Swivel chair with low back (5 spoke aluminum swivel base on casters + gas lift) 301632-410 Certificate Number

05/15/2023 - 04/27/2026

**Certificate** Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.

Furniture and furnishings are tested in accordance with ANSI/BIFMA M7.1-2011 and determined to comply with ANSI/BIFMA X7.1-2011 and ANSI/BIFMA e3-2012 Credit 7.6.1. Seating products are modeled in the seating environment.



#### **GREENGUARD Certification Criteria for Mattresses, Bedding, Component Materials and** Seating Units

Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC <sub>(A)</sub>	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	µg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	µg/m³
Individual VOCs (D)	-	1/10th TLV	-

(A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.

- (B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.
- <sup>(C)</sup> Applicable to flooring and furniture, including component materials.
- (D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).





PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS UL.COM/GG UL 2818

### INCLASS

# KORI Swivel chair with low back (4 spoke aluminum swivel base)

301633-410 Certificate Number

05/15/2023 - 04/27/2026

**Certificate** Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.

Furniture and furnishings are tested in accordance with ANSI/BIFMA M7.1-2011 and determined to comply with ANSI/BIFMA X7.1-2011 and ANSI/BIFMA e3-2012 Credit 7.6.1. Seating products are modeled in the seating environment.



#### **GREENGUARD Certification Criteria for Mattresses, Bedding, Component Materials and** Seating Units

Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC <sub>(A)</sub>	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	µg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	µg/m³
Individual VOCs (D)	-	1/10th TLV	-

(A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.

- (B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.
- <sup>(C)</sup> Applicable to flooring and furniture, including component materials.
- (D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).

