VARYA TAPIZ designed — Simon Pengelly



All GREENGUARD Gold Certified products are on <u>UL,SPOT</u>.
Please visit it for the latest update.



INCLASS

Overview



Chair 4 leg (stackable) VAR0610 <u>certificate+</u>



Armchair 4 leg VAR0618 <u>certificate+</u>



Chair sled frame VAR0620 certificate+



Armchair sled frame VAR0628 certificate+



Chair 4 leg (non stackable) VAR0615 <u>certificate+</u>



Chair 4 wooden leg VAR0630MA <u>certificate+</u>



Chair 4 plastic leg VAR0617 <u>certificate+</u>



Chair cantilever frame VAR0652 <u>certificate+</u>



Armchair cantilever frame VAR0654 <u>certificate+</u>



Chair 4 spoke steel swivel base VAR0650 certificate+



Chair 4 spoke aluminum swivel base VAR0640 <u>certificate+</u>



Chair 4 spoke aluminum swivel base on casters VAR0645 <u>certificate+</u>



Chair 5 spoke aluminum swivel base on casters VAR0647 <u>certificate+</u>



Chair 4 leg frame on casters VAR0632 <u>certificate+</u>



Chair 4 leg frame on casters+ basket VAR0634 certificate+



High chair 4 leg frame VAR0679 <u>certificate+</u>



Counter chair 4 leg frame VAR0677 <u>certificate+</u>



High chair sled frame VAR0669 <u>certificate+</u>



Counter chair sled frame VAR0667 <u>certificate+</u>



Stool sled frame (high) VAR0665 <u>certificate+</u>



Stool sled frame (medium) VAR0660 <u>certificate+</u>



Stool 4 spoke steel swivel base (high) VAR0685 certificate+



Stool 4 spoke steel swivel base (medium) VAR0680 certificate+



Stool 4 leg (high) VAR0675 <u>certificate+</u>



Stool 4 leg (medium) VAR0670 <u>certificate+</u>



Stool 4 wooden leg (high) VAR0695MA <u>certificate+</u>



Stool 4 wooden leg (medium) VAR0690MA <u>certificate+</u>



Bench VAR0750 - VAR0740 - VAR0730 - VAR0720 certificate+

Optional items & accessories



Detachable arm (right/left) Only suitable for chairs with 4 leg frame on casters VAR0036 - VAR0037 certificate+



Set of tube arms
Only suitable for
swivel bases
VAR0100 certificate+



certificate+

rms Detachable arm
if or with writing tablet
is (right/left)
icate+ Only suitable for
chairs with 4 leg
frame on casters
VAR0038 - VAR0039



Writing tablet (right/left) Only suitable for 4 leg chairs and sled base chairs VAR0160 - VAR0162 VAR0164 - VAR0166 certificate+



INCLASS

VARYA TAPIZ Chair with 4 leg frame (stackable)

227870-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA TAPIZ Armchair with 4 leg frame

227871-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA TAPIZ Chair with sled frame

227875-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA TAPIZ Armchair with sled frame

227876-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA TAPIZ Chair with 4 leg frame (non stackable)

227872-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA TAPIZ Chair with 4 wooden leg frame

227873-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (c)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA TAPIZ Chair 4 plastic leg frame

227874-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA TAPIZ Chair with cantilever frame

227877-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA TAPIZ Armchair with cantilever frame

227878-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (c)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA TAPIZ Chair with 4 spoke steel swivel base

227879-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA TAPIZ Chair with 4 spoke aluminum swivel base

227880-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA TAPIZ Chair with 4 spoke aluminum swivel base with casters

227881-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA TAPIZ Chair with 5 spoke aluminum swivel base with casters

227882-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA TAPIZ Chair with 4 leg frame on casters

227883-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA TAPIZ Chair with 4 leg frame on casters + basket

227884-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA TAPIZ High chair with 4 steel leg frame

227893-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA TAPIZ Counter chair with 4 steel leg frame

227894-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA TAPIZ High chair with sled frame

227895-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA TAPIZ Counter chair with sled frame

227896-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA TAPIZ Stool with sled frame (high)

227887-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA TAPIZ Stool with sled frame (medium)

227888-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA TAPIZ Stool with 4 spoke steel swivel frame (high)

227889-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA TAPIZ Stool with 4 spoke steel swivel frame (medium)

227890-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA TAPIZ Stool with 4 leg frame (high)

227885-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA TAPIZ Stool with 4 leg frame (medium)

227886-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (c)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA TAPIZ Stool with 4 wooden leg (high)

227891-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (c)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA TAPIZ Stool with 4 wooden leg (medium)

227892-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA TAPIZ Seat for bench

227897-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA 5 seater bench frame with legs (seats not included)

227852-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA 4 seater bench frame with legs (seats not included)

227853-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA 3 seater bench frame with legs (seats not included)

227854-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (c)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA 2 seater bench frame with legs (seats not included)

227855-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA Detachable arm (right/left) *Only suitable for chairs with 4 leg frame on casters

227863-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA Set of tube arms *Only suitable for swivel bases

227862-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA Detachable arm with writing tablet (right/left) *Only suitable for chairs with 4 leg frame on casters

227866-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA Writing tablet (right/left)
*Only suitable for 4 leg chairs

227864-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



INCLASS

VARYA Writing tablet (right/left)
*Only suitable for sled base chairs

227865-410

Certificate Number

04/27/2021 - 04/27/2026

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.



Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.25	mg/m³
Formaldehyde	50-00-0	30.7 (25 ppb)	μg/m³
Total Aldehydes (B)	-	0.05	ppm
4-Phenylcyclohexene (C)	4994-16-5	3.25	μg/m³
Individual VOCs (D)	-	1/10th TLV	-

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.



⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Applicable to flooring and furniture, including component materials.

⁽D) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).